



Free Questions for [DES-4421](#) by [braindumpscollection](#)

Shared by [Randolph](#) on [24-05-2024](#)

For More Free Questions and Preparation Resources

[Check the Links on Last Page](#)

Question 1

Question Type: MultipleChoice

A new administrator has just taken over an MX7000 Multi-Chassis Management Group and two-racks of PowerEdge servers. The previous administrator no longer works at the company and is not available. No one knows the password for the OME-M interface and the default password is not working.

What must be used to reset the password?

Options:

- A- iDRAC for one of the compute sleds.
- B- Left ear control panel.
- C- RACADM using a serial connection
- D- Management Module jumpers

Answer:

D

Question 2

Question Type: MultipleChoice

What is a benefit of SmartFabric Services Mode?

Options:

- A- Topology validation and self-healing
- B- Load balancing for management layers
- C- Load balancing for application layers
- D- Automatic detection of packet collisions

Answer:

B

Question 3

Question Type: DragDrop

A technician is deploying a new MX7000 chassis using the Chassis Deployment Wizard.

What is the correct order of steps followed by the wizard?

Configure iDRAC and IOM Quick Deploy Settings	STEP 1
Answer: Import Profile or join Multi-chassis Group	STEP 2
Configure Activity and Alerts	STEP 3
Define Groups	STEP 4
Update Firmware and configure Proxy	STEP 5

Question 4

Question Type: MultipleChoice

An administrator is configuring a fully populated MX5016s storage sled to be accessed by four MX740c compute sleds. Each compute sled has an H745P Jumbo PERC installed. The disks in the storage sled are evenly distributed across all compute sleds using a Drive-Assigned storage configuration.

What is the maximum number of disks that each compute sled can detect from the MX5016s?

Options:

A- 1

B- 2

C- 4

D- 16

Answer:

D

Question 5

Question Type: MultipleChoice

What is the number of server-facing ports and the bandwidth of each port on the MXG610s? (Choose two.)

Options:

A- 8x 16 Gbps

B- 16x 32 Gbps

C- 16x 16 Gbps

D- 8x 32 Gbps

Answer:

B, C

Question 6

Question Type: MultipleChoice

What is a function of the Fabric Resources Director (FReD)?

Options:

- A- SAS Expander routing for Fabric C
- B- Hosting OME-M interface
- C- Critical temperature monitoring
- D- Providing QuickSync 2 feature

Answer:

C

Question 7

Question Type: DragDrop

A datacenter administrator has been tasked to perform firmware updates of the whole chassis and its components based on the latest dell.com catalog.

What is the correct sequence of actions?

Click Compliance Report	STEP 1
Answer: Add a Catalog	STEP 2
Select Target Devices or Groups	STEP 3
Navigate to Configuration > Firmware menu	STEP 4
Create a Baseline	STEP 5

Question 8

Question Type: MultipleChoice

What is a characteristic of MX7000 networking in Scalable Fabric Mode?

Options:

- A-** Enabled by default, all switch-specific OS10EE capabilities are available.
- B-** Layer 2 bridging is disabled by default and interfaces must join a bridge domain (VLAN) before being able to forward frames.
- C-** All switch interfaces are assigned to VLAN 1 by default and are in the same Layer 2 bridge domain.
- D-** Available on MX9116n FSE and MX7116n FEM but not on the MX5108n.

Answer:

D

To Get Premium Files for DES-4421 Visit

<https://www.p2pexams.com/products/des-4421>

For More Free Questions Visit

<https://www.p2pexams.com/dell-emc/pdf/des-4421>

