



Free Questions for H19-424_V1.0 by [braindumpscollection](#)

Shared by [Lewis](#) on [24-05-2024](#)

For More Free Questions and Preparation Resources

[Check the Links on Last Page](#)

Question 1

Question Type: MultipleChoice

In the sales strategy of campus network products, when there are more APs in a single project, after-sales network planning service 1 must be carried out

Options:

A- 100

B- 200

C- 300

D- 400

Answer:

A

Question 2

Question Type: MultipleChoice

In the campus SDN solution, the statement about the distributed gateway solution is wrong ()

Options:

- A-** Distributed gateway - VxLAN to access, independent AC scenario, for wireless traffic, local forwarding mode is not recommended.
- B-** Distributed gateway - VxLAN to access, independent AC scenario, from the edge to the VN, on the edge to execute the service accompanying policy (the edge needs to subscribe to the IP-Group service), the current solution has supported automatic deployment.
- C-** The VTEP device is both an L2 gateway and an L3 gateway. The non-gateway node is not aware of the VXLAN tunnel and acts only as the forwarding node for VXLAN packets.
- D-** Distributed gateway - VxLAN to aggregation, AC on the board, the wireless traffic service accompanying policy is executed on the edge, and tunnel forwarding is recommended.

Answer:

B

Question 3

Question Type: MultipleChoice

For the description of the WLAN network planning scheme in the dormitory/hotel one-in-two scene with a bathroom at the door, the correct one is ()

Options:

- A-** Select butterfly wing wave AP wall-mounted bathroom corner, height 2.2~2.5m, a single AP covers the left and right 2 rooms
- B-** The AP fixes the radio power and configures the maximum EIRP to improve the downlink coverage of the room through the wall, with the worst 5G downlink RSSI being -65dBm and the worst uplink RSSI being -80dBm
- C-** Indoor omnidirectional APs (2*2 models such as 5761-11) are deployed separately in the corridor to ensure roaming continuity
- D-** The bathroom relies on 5G for coverage and turns off 2.4G

Answer:

D

Question 4

Question Type: MultipleChoice

switch V600R022 version, about the PV6 RGuard implementation description, the incorrect is ()

Options:

- A-** RA packets can carry a lot of network configuration information, including the default router, network prefix list, and whether to use a DHCPv6 server for stateful address allocation. An attacker can send forged RA packets to modify the network configuration of the user's host so that legitimate users cannot communicate properly. IPv6RGuard provides a defense mechanism against RA packet attacks, which can effectively prevent such network attacks.
- B-** Configure the host or router role for the interface, and then the device can forward or discard RA packets based on the interface role.
- C-** If the interface is connected to the user host, the interface role is set to host, and if the interface is connected to the router, the administrator can configure the interface role to router according to the interface networking. Version 22.0 also supports policy-based filtering of ND packets.
- D-** 22.0 also supports policy-based filtering of ND packets.

Answer:

D

Question 5

Question Type: MultipleChoice

The current controller does not support which of the following authentication methods?

Options:

A- Portal

B- TACACS

C- P2P

D- 802.1X

Answer:

C

Question 6

Question Type: MultipleChoice

The maximum channel bandwidth supported by WIFI6 is:

Options:

A- 80M

B- 160M

C- 320M

D- 640M

Answer:

B

Question 7

Question Type: MultipleChoice

For the sake of WLAN security, if the customer wants to manage the WLAN data in a unified manner, the customer can choose which of the following networking methods:

Options:

A- AC side-attached data is forwarded directly

B- AC side-attached data tunnel forwarding

C- Layer 3 networking data is forwarded directly

D- Layer 2 networking data is forwarded directly

Answer:

B

Question 8

Question Type: MultipleChoice

iMaster NCE-Campus is deployed in a virtualized environment based on Taishan's physical server, and the corresponding virtualization software is:

Options:

A- FusionCompute8.0

B- FusionCompute6.5.1

C- VNWare vSphere

D- FusionInsight

Answer:

A

Question 9

Question Type: MultipleChoice

Regarding planning and design tools, the following statements are wrong

Options:

- A-** The planning and design tool is used for after-sales planning and cannot be used before sales
- B-** When the equipment model cannot be used, you can feedback it in the tool platform
- C-** The tool can ensure the logical consistency and data consistency of the design
- D-** In the case of large or frequent changes in the network, the old project can be retained and the new project can be designed

Answer:

A

Question 10

Question Type: MultipleChoice

Configure the main interface of the translation tool, and some lines are marked with different background colors for the purpose of ()

Options:

- A-** The relocation is too boring, and the interface is too monotonous, purely for decoration and good looks
- B-** Remind users of the points that need special attention, such as: those that need to be manually confirmed and processed, and those that can be discarded
- C-** In order to export the configuration, the configuration does not have the background color everywhere when exporting the configuration
- D-** It has no practical effect

Answer:

B

Question 11

Question Type: MultipleChoice

In the CloudCampus APP, a maximum of () images can be uploaded to a survey site

Options:

A- 1

B- 2

C- 3

D- 4

Answer:

C

Question 12

Question Type: MultipleChoice

The following scenarios in the CloudCampus solution do not belong to external network interconnection:

Options:

A- L3 shared exit

B- L3 exclusive export

C- Shared export

D- L2 exclusive export

Answer:

D

To Get Premium Files for H19-424_V1.0 Visit

https://www.p2pexams.com/products/h19-424_v1.0

For More Free Questions Visit

<https://www.p2pexams.com/huawei/pdf/h19-424-v1.0>

