

Free Questions for H31-611 by certscare

Shared by Crawford on 24-05-2024

For More Free Questions and Preparation Resources

Check the Links on Last Page

Question 1

Question Type: MultipleChoice

The SDN controller has a global view of the entire network.

Options:

A- TRUE

B- FALSE

Answer:

Α

Question 2

Question Type: MultipleChoice

Which of the following interfaces are provided by SDN reflect programmability? (Multiple Choice)

| | 4.5 | | | |
|-----|-----|--------------|-----|--|
| () | ntı | \mathbf{O} | 16. | |
| V | pti | VI | 13. | |

- A- Northbound interface
- **B-** Southbound interface
- C- Eastbound-westbound interface
- D- API PLC programming interface

Answer:

A, B

Question 3

Question Type: MultipleChoice

Which OpenStack component is responsible for managing virtual networks and determining the ID of the server that the VM IP address, VM MAC address, and VM belong to?

Options:

A- Nova

| B- Neutron | |
|--------------------------------------|--|
| C- Cinder | |
| D- NetMatrix | |
| | |
| Answer: | |
| D | |
| | |
| | |
| | |
| Question 4 | |
| | leChoice |
| QUESTION 4 Question Type: Multip | leChoice |
| uestion Type: Multip | leChoice nitecture comprises which of the following components? (Multiple Choice) |
| uestion Type: Multip | |
| uestion Type: Multip | |
| uestion Type: Multip | |
| The OpenStack arc Options: | |
| The OpenStack arc Options: | |
| The OpenStack arc Options: A- Nova | |

| Answer: |
|--|
| C, D |
| |
| Question 5 |
| uestion Type: MultipleChoice |
| In the SDN architecture, which of the following protocols is used for communication between the control layer and application layer? |
| Options: |
| A- OpenFlow |
| B- NETCONF |
| C- RESTful |
| D- NetStream |
| |
| Answer: |
| A |

Question 6

Question Type: MultipleChoice

On a VXLAN network, which of the following statements are NOT true about VNIs? (Multiple Choice)

Options:

- A- A VNI is a VXLAN network identifier used to differentiate VXLAN segments.
- B- One VNI identifies one tenant, regardless of whether the tenant contains multiple end users.
- C- VMs of different VXLAN segments cannot directly communicate with each other at Layer 2.
- D- A VNI consists of 16 bits.

Answer:

B, C, D

Question 7

Question Type: MultipleChoice

| Options: | | | |
|----------|--|--|--|
| A- TRUE | | | |
| B- FALSE | | | |
| | | | |
| | | | |
| Answer: | | | |

On an SDN network, network devices only need to be responsible for- data forwarding.

В

To Get Premium Files for H31-611 Visit

https://www.p2pexams.com/products/h31-611

For More Free Questions Visit

https://www.p2pexams.com/huawei/pdf/h31-611

