



**Free Questions for 500-920 by certsdeals**

**Shared by Allison on 24-05-2024**

**For More Free Questions and Preparation Resources**

**Check the Links on Last Page**

## Question 1

---

**Question Type:** MultipleChoice

---

When booting up a Cisco UCS Server you want to see boot time diagnostic messages of the POST, what action is required for you to do so?

### Options:

---

- A- Enable Quiet Boot on the Server's BIOS
- B- Restart the Server
- C- Disable Fast Boot on the Server's BIOS
- D- Enable Quiet Boot on the Server's Service Profile
- E- Disable Fast Boot on the Server's Service Profile

### Answer:

---

D

## Question 2

---

**Question Type: MultipleChoice**

---

Which two formats can be configured for Cisco's Call Home email message? (Choose two )

**Options:**

---

A- JSON

B- CSV

C- Full text

D- XML

**Answer:**

---

C, D

**Explanation:**

---

Call Home Message Formats The Call Home feature offers the following message formats: \* Short Text --- Suitable for pagers or printed reports. \* Plain Text --- Full formatted message information suitable for human reading. \* XML --- Matching readable format using Extensible Markup Language (XML) and Adaptive Markup Language (AML) document type definitions (DTDs). The XML format enables communication with the Cisco TAC. For user-defined destination profiles, the format options are long-text, short-text, or XML. The default is XML. For the predefined Cisco TAC profile, only XML is allowed.

## Question 3

---

**Question Type:** MultipleChoice

---

When troubleshooting, which option is the primary uses of the SCOPE command?

**Options:**

---

- A- To access the log files on the log server
- B- The SCOPE command is not helpful in this case
- C- To access the log files on the virtual machines
- D- To access the log files that reside in a component

**Answer:**

---

D

## Question 4

---

**Question Type:** MultipleChoice

---

A new UCS dual fabric cluster is being configured with a single chassis. The administrator notices that the cluster is not in High Availability (HA) mode. What is the possible cause?

### Options:

---

- A- No uplinks are active into the data center.
- B- The links to the chassis are not enabled
- C- The HA plugin has not been installed in UCS Manager
- D- The UCS-FI-HA license has not been activated in UCS Manager

### Answer:

---

C

## Question 5

---

**Question Type:** MultipleChoice

---

Which Cisco UCS internal component maintains the UCS XML database, manages the FSM stages and operations and instructs the Application Gateway to perform operations on physical and logical elements?

**Options:**

---

- A- Cisco Data Management Engine
- B- Cisco UCS Manager
- C- Cisco Application Gateways
- D- Cisco Finite State Machine

**Answer:**

---

A

**Explanation:**

---

[https://www.cisco.com/c/en/us/td/docs/unified\\_computing/ucs/ucs-manager/GUI-User-Guides/System-Monitoring/3-1/b\\_UCSM\\_GUI\\_System\\_Monitoring\\_Guide\\_3\\_1/b\\_UCSM\\_GUI\\_System\\_Monitoring\\_Guide\\_3\\_1\\_chapter\\_0100.html](https://www.cisco.com/c/en/us/td/docs/unified_computing/ucs/ucs-manager/GUI-User-Guides/System-Monitoring/3-1/b_UCSM_GUI_System_Monitoring_Guide_3_1/b_UCSM_GUI_System_Monitoring_Guide_3_1_chapter_0100.html)

## Question 6

---

**Question Type:** MultipleChoice

---

Which two interfaces allow access to Cisco UCS Manager? (Choose two )

### Options:

---

- A- Cisco KVM
- B- Cisco UCS Manager XML API
- C- Cisco IMC
- D- Cisco UCS Manager GUI

### Answer:

---

B, D

## Question 7

---

**Question Type:** MultipleChoice

---

What three options should be verified, when you are able to connect to Cisco UCS Manager, but unable to open a KVM session to a blade? (Choose three)

**Options:**

---

- A-** Verify TCP port 2068 is not blocked by an ACL or Firewall
- B-** Confirm the IP Address assigned to UCS Manager is the same as the KVM address
- C-** Verify the KVM IP Address is on the same ip subnet as the virtual machines
- D-** Confirm the KVM IP Address is added to the route table in Cisco UCS Manager
- E-** Confirm the IP Address assigned to the KVM is not a duplicate IP
- F-** Verify the KVM IP Address is on the same subnet as the Fabric Interconnect management address

**Answer:**

---

A, D, E

## Question 8

---

**Question Type:** MultipleChoice

---



After installing a new UCS M4 server, which two Cisco Integrated Management Controller connectivity options do you have? (Choose two )

**Options:**

---

- A- XML API Access
- B- Web Access
- C- In-band Access
- D- SNMP
- E- Out-of-Band Access

**Answer:**

---

A, C

## Question 9

---

**Question Type: MultipleChoice**

---

When troubleshooting a LAN connectivity issue, you notice a failed uplink from the Cisco UCS Fabric Interconnects to the upstream LAN switch. What two could be causing the issue? (Choose two )

### Options:

---

- A- Misconfigured VLAN on the failed uplink
- B- Misconfigured QoS parameters on the failed uplink
- C- A port channel mismatch between the Fabric Interconnects and the upstream LAN switch
- D- A SFP Type mismatch between the Fabric Interconnects and the upstream LAN switch
- E- A port speed configuration mismatch between the Fabric Interconnects and the upstream LAN switch

### Answer:

---

B, C

**To Get Premium Files for 500-920 Visit**

**<https://www.p2pexams.com/products/500-920>**

**For More Free Questions Visit**

**<https://www.p2pexams.com/cisco/pdf/500-920>**

