



Free Questions for 300-620 by go4braindumps

Shared by Briggs on 09-08-2024

For More Free Questions and Preparation Resources

Check the Links on Last Page

Question 1

Question Type: MultipleChoice

A network administrator configures AAA inside the Cisco ACI fabric. The authentication goes through the local users if the TACACS+ server is not reachable. If the Cisco APIC is out of the cluster, the access must be granted through the fallback domain. Which configuration set meets these requirements?

Options:

A- Ping Check: True

Default Authentication Realm: Local

Fallback Check: True

B- Ping Check: True

Default Authentication Realm: TACACS+

Fallback Check: False

C- Ping Check: False

Default Authentication Realm: Local

Fallback Check: False

D- Ping Check: False

Default Authentication Realm: TACACS+

Fallback Check: True

Answer:

D

Question 2

Question Type: MultipleChoice

A customer creates Layer 3 connectivity to the outside network. However, only border leaf switches start receiving destination updates to other networks from the newly created L3Out. The updates must also be propagated to other Cisco ACI leaf switches. The L3Out is linked with the EPGs via a contract. Which action must be taken in the pod policy group to accomplish this goal?

Options:

- A- Apply a BGP route reflector policy.
- B- Enable a COOP policy.
- C- Configure an IS-IS policy.
- D- Implement an access management policy.

Answer:

A

Question 3

Question Type: MultipleChoice

Refer to the exhibit.



Refer to the exhibit, An engineer is deploying a Cisco ACI environment but experiences a STP loop between switch1 and switch2. Which configuration step is needed to break the STP loop?

Options:

- A-** Configure the STP instance to VLAN mapping under the switch STP policy.
- B-** Configure a Layer 2 external bridged network on the interfaces facing the MST switches.
- C-** Enable the native VLAN on the interfaces facing the MST switches using static pons in a dedicated EPG.
- D-** Enable BPDU filter under the STP interface policy on the Interfaces lacing the MST switches.

Answer:

C

Question 4

Question Type: MultipleChoice

Refer to the exhibit.

Properties

Name: Rostan-oob-mgmt-01

Type: ALL ALL_IN_POOL range

Node Blocks:

| From | To |
|------|-----|
| 1 | 1 |
| 101 | 101 |
| 102 | 102 |
| 201 | 201 |

Nodes Within The Policy:

| ID | Name | Out-of-Band Management IP | Out-of-Band Management Gateway | In-Band Management IP | In-Band Management Gateway |
|-----|---------|-----------------------------------|--------------------------------|-------------------------|----------------------------|
| 1 | apic1 | 172.16.31.85 fe80::200:f:fe0:0 | 172.16.31.254/24 | 192.168.11.1 fc00::1 | |
| 101 | leaf-1 | 20.0.254.101 ... | 20.0.254.1 | -- | |
| 102 | leaf-2 | 20.0.254.102 ... | 20.0.254.1 | -- | |
| 201 | spine-1 | 172.16.31.84 ... | 172.16.31.254/24 | -- | |

Refer to the exhibit A Cisco ACI fabric is using out-of-band management connectivity The APIC must access a routable host with an IP address of 192 168 11 2 Which action accomplishes this goal?

Options:

A- Change the switch APIC Connectivity Preference to in-band management

- B-** Remove the in-band management address from the APIC.
- C-** Add a Fabric Access Policy to allow management connections.
- D-** Modify the Pod Profile to use the default Management Access Policy

Answer:

B

Question 5

Question Type: MultipleChoice

Refer to the exhibit.

Create Configuration Export Policy

Name: *

Description: optional

Format: json xml

Start Now: Yes No

Target DN:

Snapshot:

Scheduler:

Export Destination: *

Modify Global AES Encryption Settings: Enabled

Cancel Submit

Refer to the exhibit A customer must back up the current Cisco ACI configuration securely to the remote location using encryption and authentication. The backup job must run once per day The customer s security policy mandates that any sensitive information including passwords, must not be exported from the device Which set of steps meets these requirements?

- Export destination using FTP protocol.
Use XML format.
- Export destination using SCP protocol.
Disable Global AES Encryption.
- Export destination using SCP protocol.
Use XML format.
- Export destination using FTP protocol.
Disable Global AES Encryption.

Options:

A- Option A

B- Option B

C- Option C

D- Option D

Answer:

B

Question 6

Question Type: MultipleChoice

Which class of ACL object is presented in this output?

```
test_apic1# moquery -c {output_omitted}
Total Objects shown: 1
```

```
name: test1
childAction:
descry:
dn: uni/tn-test
lcOwn: local
modTs: 2020-12-01T06:04:35.064+00:00
monPolDn: uni/tn-common/monepg-default
ownerKey:
ownerTag:
rn: tn-test
status:
uid: 389457021
```

Options:

- A- Contract
- B- Bridge Domain
- C- Tenant

D- Endpoint

Answer:

A

Explanation:

<https://www.cisco.com/c/en/us/td/docs/switches/datacenter/aci/apic/sw/4-x/openstack/ACI-Installation-Guide-for-Red-Hat-Using-OSP13-Director/m-configuring-ironic-for-openstack.html>

Question 7

Question Type: MultipleChoice

An engineer must deploy Cisco ACI across 10 geographically separated data centers. Which ACI site deployment feature enables the engineer to control which bridge domains contain Layer 2 flooding?

Options:

- A- GOLF
- B- Multi-Site
- C- Multi-Pod
- D- Stretched Fabric

Answer:

B

Explanation:

https://www.cisco.com/c/en/us/td/docs/switches/datacenter/aci/aci_multi-site/sw/2x/fundamentals/Cisco-ACI-Multi-Site-Fundamentals-Guide-211/Cisco-ACI-Multi-Site-Fundamentals-Guide-211_chapter_011.html#id_51188

From the web page, we see that multi-site has control over:

Stretched Bridge Domain with Layer 2 Broadcast Extension.

Stretched Bridge Domain with no Layer 2 Broadcast Extension.

Question 8

Question Type: MultipleChoice

Which routing protocol is supported between Cisco ACI spines and IPNs in a Cisco ACI Multi-Pod environment?

Options:

- A- OSPF
- B- ISIS
- C- BGP
- D- EIGRP

Answer:

C

Explanation:

BGP is supported between Cisco ACI spines and IPNs in a Cisco ACI Multi-Pod environment.

To Get Premium Files for 300-620 Visit

<https://www.p2pexams.com/products/300-620>

For More Free Questions Visit

<https://www.p2pexams.com/cisco/pdf/300-620>

