



Free Questions for 300-625 by certsinside

Shared by Bush on 24-05-2024

For More Free Questions and Preparation Resources

Check the Links on Last Page

Question 1

Question Type: MultipleChoice

A storage network engineer is implementing disk-array data replication between two SAN environments in two different data centers not connected via Fibre Channel. Which SAN switch feature must be implemented?

Options:

- A- FCIP
- B- zoning merge over LAN
- C- VSAN scoping
- D- IVR

Answer:

A

Question 2

Question Type: MultipleChoice

Which configuration is available only in Cisco DCNM-SAN Advanced mode?

Options:

- A- IVR
- B- VMpath configuration
- C- zoning
- D- template-based provisioning

Answer:

A

Question 3

Question Type: MultipleChoice

Which Cisco NX-OS command displays the VSAN that is associated with each FCID?

Options:

- A- show fcdomain
- B- show fc2 plogi
- C- show vsan database
- D- show flogi database

Answer:

A

Question 4

Question Type: MultipleChoice

After user account attributes are modified in Cisco NX-OS, when do changes to the user's session attributes take effect?

Options:

- A- immediately

- B- at the scheduled time
- C- when the user logs out of a session
- D- when the user creates a new session

Answer:

D

Question 5

Question Type: MultipleChoice

A Cisco MDS Series Switch with the POAP feature boots and does not find the startup configuration. Which location is checked first when the switch enters POAP mode?

Options:

- A- USB device that contains the software image files and the switch configuration file
- B- DHCP server to bootstrap the interface IP address, gateway, DNS server, and TFTP IP addresses
- C- TFTP server where the necessary configuration files are downloaded

D- HTTP server where the URL is used to download the software image

Answer:

A

Question 6

Question Type: MultipleChoice

Which two components are required for successful MDS USB POAP (Choose two.)

Options:

- A-** NTFS formatted USB drive
- B-** USB drive in port 1
- C-** script named poap_script.pl
- D-** ENTERPRISE_PKG license
- E-** system and kickstart images

Answer:

C, E

Question 7

Question Type: DragDrop

Drag and drop the mechanisms of Cisco Secure Boot from the left into the correct order on the right.

Validate the Cisco digital signature on the next set of instructions.

Step 1

Answer:

The operating system is launched if all the checks are passed.

Step 2

Question 8

The microloader instruction set is stored in a genuine hardware anchor.

Step 3

Question Type: MultipleChoice

Validate the genuineness of the device operating system.

Step 4

A network engineer must run a core Cisco Nexus 9500 Series Switch as a POAP server for all top of rack Cisco Nexus switches. Which two network functions must run to provide the POAP service? (Choose two.)

Options:

- A- DNS
- B- PXE
- C- BOOTP
- D- TFTP
- E- DHCP

Answer:

D, E

Question 9

Question Type: MultipleChoice

Which component is initially responsible for loading the kickstart image on Cisco MDS Switches?

Options:

A- ROMMON

B- BIOS

C- NX-OS

D- BASH

Answer:

C

To Get Premium Files for 300-625 Visit

<https://www.p2pexams.com/products/300-625>

For More Free Questions Visit

<https://www.p2pexams.com/cisco/pdf/300-625>

