

# Free Questions for 300-915 by dumpshq

Shared by Jordan on 24-05-2024

For More Free Questions and Preparation Resources

**Check the Links on Last Page** 

# **Question 1**

### **Question Type:** MultipleChoice

An IoT application has been built into the application CI/CD pipeline. The application needs credentials to access other applications, APIs, and cloud resources.

When should the credentials be inserted into the application using the CI/CD process?

### **Options:**

- A- hard coded into your application code base
- B- during application runtime
- C- after application testing
- D- during application build time

#### **Answer:**

Α

# **Question 2**

### **Question Type:** MultipleChoice

The environment for an Industrial IoT project in a large open pit mine is being scoped. The location has a large amount of dust and the device will be exposed to less than 1 meter of water temporarily.

When the edge device is being chosen, which Ingress protection rating must be used?

### **Options:**

**A-** IP37

**B-** IP61

**C-** IP67

**D-** IP76

#### **Answer:**

C

# **Question 3**

**Question Type:** DragDrop

An engineering team developed a solution that gathers data via a proprietary protocol (TCP/IP based) to a IR1101 gateway, which then sends the data to the cloud. Drag and drop the action steps from the left into the correct order on the right to get this solution to operate. Not all options are used.

The sensor is sending data to the cloud.		
Answer: The sensor and IR1101 is locally installed (power, network connectivity).		
Question phication is being installed on the IR1101.		
Question Type: MultipleChoice The streaming payload is visible in Kinetic GMM		
Which two statements define the methanism for console access of	the Gu	est Operating System from the Cisco IR829 router? (Choose
A device twin is automatically created in the cloud.		
Option 101 is claimed via API on Kinetic GMM.		

- A- The Guest OS can be accessed by default on Telnet port 2070 from the Cisco IR829 console.
- B- The Guest OS console is available directly by the AUX port 3362 from the Cisco IR829 router.
- C- The Guest OS can be accessed directly using the console port on the Cisco IR829 router.

- D- The Guest OS can be accessed by initiating SSH from the Cisco IR829 console.
- E- The Guest OS console is available only when a static IP is configured on the host.

#### **Answer:**

A, D

# **Question 5**

**Question Type:** MultipleChoice

What is a major difference of MQTT in terms of design compared to AMQP?

### **Options:**

- A- MQTT requires more bandwidth.
- B- MQTT has very low overhead.
- **C-** MQTT has more advanced routing features for messages.
- D- MQTT provides routing based on headers.


### **Answer:**

В

# **Question 6**

**Question Type:** MultipleChoice

Refer to the exhibit.



Which two statements about data flow are true? (Choose two.)

#### **Options:**

- A- Another AMQP broker should be implemented on the customer cloud.
- B- Instead of AMQP, MQTT should be used for compatibility issues in a cloud-to-cloud connection.
- C- A VPN tunnel is not necessary because the MQTT payload is encrypted by default.
- D- The gateway must stay constantly connected to the Kinetic cloud to avoid blank data sets, even when using caching functions.
- **E-** The Python application could use the paho-mqtt library.

#### **Answer:**

B, E

# **Question 7**

**Question Type:** MultipleChoice

Refer to the exhibit.

```
descriptor-schema-version: "2.4"
info:
 name: hello world
  description: "Hello world lxc type application"
 version: "1.0"
  author-link: "http://www.cisco.com"
  author-name: "Cisco Systems"
app:
  type:
  cpuarch: x86 64
  resources:
    profile: custom
   cpu: 200
   memory: 64
   disk: 2
    network:
        interface-name: eth0
  # Specify runtime and startup
  startup:
    rootfs: rootfs.tar
    target: "/var/helloworld/helloworld"
```

While troubleshooting an error on an application descriptor for a Docker app in Cisco IOx (package.yaml), the app type appears to be missing. Which app type must be added to the snippet to resolve the issue?

A- paas					
B- docker-vm					
C- docker					
D- docker-app					
Answer:					
C					
C					
C					
c Question 8					
uestion 8	Na dia a				
	Choice				
Question 8  Destion Type: Multiple					
Question 8  Destion Type: Multiple	<b>Choice</b> uter (IR) and switch (IE) por	tfolio support edge da	ta services?		
Question 8  Destion Type: Multiple		tfolio support edge da	ta services?		
Question 8  Destion Type: Multiple		tfolio support edge da	ta services?		
Question 8  Destion Type: Multiple		tfolio support edge da	ta services?		

- B- Edge data services can run only in virtual machines on a separate compute layer.
- C- Edge data services are aliases for IR/IE configuration services.
- D- Edge data services run as separate instances only on virtual machines.

#### **Answer:**

C

# **Question 9**

#### **Question Type: DragDrop**

An application needs to calculate if the product meets a determined quality specification, activate an automation to remove poor quality products, and report detailed results back to the cloud. All data are captured from an application that is connected to a sensor. Using the SDK of the cloud provider, drag and drop the tasks that must be completed from the left to the right. Not all options are used.

code function for detection	
Answer: quality specification of product	
credentials for network and cloud operations	
Question with sensor SDK	
Question Type Maniple Caction with the application	
cloud function communication with cloud SDK Refer to the exhibit.	
"/Users/veny/hin/nython" "/Users/Documents/Coding B	Projects (fly52 (main my"

```
"/Users/venv/bin/python" "/Users/Documents/Coding Projects/fkf3/main.py"
log: Sending CONNECT (u1, p1, wr0, wq0, wf0, c1, k60) client_id=b'python'
log: Sending SUBSCRIBE (d0, m1) [(b'eschbornoffice/things/FCD6BD00001913F4/uplink', 0)]
log: Sending SUBSCRIBE (d0, m2) [(b'eschbornoffice/things/FCD6BD0000191405/uplink', 0)]
log: Sending SUBSCRIBE (d0, m3) [(b'eschbornoffice/things/FCD6BD00001913FC/uplink', 0)]
log: Sending SUBSCRIBE (d0, m4) [(b'eschbornoffice/things/FCD6BD00001913F2/uplink', 0)]
log: Received CONNACK (0, 0)
Result code 0
log: Received SUBACK
log: Received SUBACK
log: Received SUBACK
log: Received SUBACK
```

Which two statements about MQTT messaging are true? (Choose two.)

### **Options:**

- A- Result code 5 means the connection is accepted; result code 0 means the connection is 'refused, not authorized'.
- B- Redundant ClientIDs are supported by MQTT brokers.
- C- MQTT does not support a 'keep alive' functionality because it runs on top of TCP.
- D- Result code 0 means the connection is accepted; result code 5 means the connection is 'refused, not authorized'.
- E- Brokers can send the Last Will and Testament messages on behalf of the client.

#### **Answer:**

D, E

# **Question 11**

#### **Question Type:** MultipleChoice

When an RS232 device is connected to a Cisco IR829 router, the data collected is not being parsed correctly by the edge application.

Which two steps should be taken to troubleshoot the issue? (Choose two.)

### **Options:**

- A- SSH access on the Cisco IR829 router must be enabled for IOx Guest OS.
- B- Communication mode must be set to half duplex over serial connection.
- C- Serial cable length should not exceed 1.5 meters.
- D- Ensure that communication parameters like baud rate and parity are set correctly.
- E- Set the cable connections based on the PIN layout from the sensor vendor.

#### **Answer:**

D, E

# **Question 12**

**Question Type:** MultipleChoice

Refer to the exhibit.

```
FROM devhub-docker.cisco.com/iox-docker/ir800/base-rootfs as builder RUN opkg update
RUN opkg install iox-toolchain
RUN mkdir -p /var/helloworld/
COPY helloworld.c /var/helloworld/
WORKDIR /var/helloworld/
RUN gcc helloworld.c -o helloworld

FROM devhub-docker.cisco.com/iox-docker/ir800/base-rootfs
RUN mkdir -p /var/helloworld/
COPY --from=builder /var/helloworld/helloworld /var/helloworld
RUN chmod +x /var/helloworld/helloworld
COPY init_app.sh /etc/init.d/
RUN chmod +x /etc/init.d/init_app.sh
RUN update-rc.d init_app.sh defaults
```

When a Docker image is built using this Dockerfile, which two statements are valid on Cisco IOx 1.8 and before? (Choose two.)

### **Options:**

- A- It builds an image that can be executed on all Cisco platforms.
- **B-** It builds a Docker image that cannot be used directly on Cisco IOx.
- C- It compiles a 'hello world' program in C.
- D- It creates two separate images.

E- It builds an IOx package that can be deployed directly.

### Answer:

B, C

### To Get Premium Files for 300-915 Visit

https://www.p2pexams.com/products/300-915

### **For More Free Questions Visit**

https://www.p2pexams.com/cisco/pdf/300-915

