



**Free Questions for 500-920 by [braindumpscollection](#)**

**Shared by [Newton](#) on [22-07-2024](#)**

**For More Free Questions and Preparation Resources**

**[Check the Links on Last Page](#)**

## Question 1

---

### Question Type: MultipleChoice

---

You are in the process of upgrading your UCS M3 Server to a newer UCS M4 Server. You associate the Service Profile to the new UCS Server, but it fails to boot. You suspect of a failed boot hard drive. You check your RAID1 Boot LUN in UCS Manager, but see no error messages. What could be causing the issue?

### Options:

---

- A- The newer Cisco UCS M4 Server is using flash drives, not hard drives
- B- The newer Cisco UCS M4 Server is using disks of larger capacity than the previous UCS M3 Server
- C- A misconfiguration on the Service Profile Local Boot Policy
- D- A misconfiguration on the Service Profile Local Disk Policy

### Answer:

---

A

## Question 2

---

**Question Type: MultipleChoice**

---

Which statement is true regarding the UCS Manager GUI is showing "Overall Status Unassociated" in the General tab for a C-series server?

**Options:**

---

- A- The server has a service profile assigned, but has connectivity issues with UCS Manager
- B- The server is not properly connected
- C- The server does not have a service profile assigned, but has been discovered by UCS Manager
- D- The server has been properly connected, but has not been discovered by UCS Manager

**Answer:**

---

B

## Question 3

---

**Question Type: MultipleChoice**

---

When troubleshooting, which option is the primary uses of the SCOPE command?

**Options:**

---

- A- To access the log files on the log server
- B- The SCOPE command is not helpful in this case
- C- To access the log files on the virtual machines
- D- To access the log files that reside in a component

**Answer:**

---

D

## Question 4

---

**Question Type:** MultipleChoice

---

A new UCS dual fabric cluster is being configured with a single chassis. The administrator notices that the cluster is not in High Availability (HA) mode. What is the possible cause?

**Options:**

---

- A- No uplinks are active into the data center.
- B- The links to the chassis are not enabled
- C- The HA plugin has not been installed in UCS Manager
- D- The UCS-FI-HA license has not been activated in UCS Manager

**Answer:**

---

C

## Question 5

---

**Question Type:** MultipleChoice

---

In Cisco UCS, there are several interfaces involved on the packet path from the vNIC through the adapter, IOM to finally reach Pi Which is the order of those interfaces, starting from the vNIC?

**Options:**

---

- A- VIF, UIF, HIF, SIR NIF
- B- VIF, UIF, HIF, NIF SIF

**C-** HIF, NIF, UIF, VIF SIF

**D-** HIF, SIF, VIF, UIF NIF

**Answer:**

---

A

## Question 6

---

**Question Type: MultipleChoice**

---

The UCS Chassis Discovery Policy has been set to four and a new chassis is connected with two links What is the resulting chassis recognition action?

**Options:**

---

**A-** The chassis will not be recognized

**B-** The Chassis Discovery Policy will automatically reset to two links, since it always tracks the physical connections

**C-** The chassis will be recognized and both links will be active

**D-** The chassis will be recognized but only one of the links will be active.

**Answer:**

---

A

## Question 7

---

**Question Type:** MultipleChoice

---

When server is booting from SAN, which command verifies the PLOGI sessions with the target?

**Options:**

---

**A-** Lunmap

**B-** Lunlist

**C-** FCMap

**D-** FClist

**Answer:**

---

B

**To Get Premium Files for 500-920 Visit**

**<https://www.p2pexams.com/products/500-920>**

**For More Free Questions Visit**

**<https://www.p2pexams.com/cisco/pdf/500-920>**

