Question 1

Which user is enabled when replicating data between active and stand-by Vaults?

Options:

A- DR

B- Backup

C- Operator

D- Auditor

Answer:

A

Question 2

What is the recommended method to determine if a PVWA is unavailable and should be disabled in a load balancing pool?

Options:

A- Monitor Port 443 on the PVWA server

B- Monitor Port 1858 on the PVWA server

C- Ping the PVWA server

D- Monitor Port 3389 on the PVWA server

Answer:

B

Question 3

Question Type: MultipleChoice

For redundancy, you want to add a secondary RADIUS server.

What must you do to accomplish this?

A- Add to the application settings of the PVWA web.config file.

B- In the PVWA vault.ini file, list each RADIUS server host address in the 'Addresses' attribute separated by commas.

C- Open the DBParm.ini on the Vault server. Add the second RADIUS server configuration settings after the first one, separated by a comma. Most Voted

D- In the PVWA web.config file, add the location element at the end of the config file. Set the path value to 'Default Web Site/PasswordVault/api/auth/pkipn/logon'.

Answer:

C

Question 4

Question Type: MultipleChoice

Which parameter must be provided when registering a primary Vault in Azure, but not in Amazon Web Services?

Options:

A- /RecPub

B- /AdminPass

C- /MasterPass

D- /RDPGateway

Answer:

D

Question 5

Question Type: MultipleChoice

Which component must be installed before the first CPM installation?

Options:

A- PTA

B- PSM

C- PVWA

D- EPM

Answer:

A

Question 6

Question Type: MultipleChoice

You are setting up a Linux host to act as an HTML 5 gateway for PSM sessions.

Which servers need to be trusted by the Linux host to secure communications through the gateway?

Options:

A- PSM and PVWA

B- PSM and CPM

C- PVWA and Vault

D- Vault and PSM

Question 7

Question Type: DragDrop

-

The installCyberArkSSHD parameter on the PSM for SSH can be set to multiple values.

Match each value to the correct condition.

Yes	Drag answer here	Yes

Answer:

No	Drag answer here	No

Question Type: **MultipleChoice**

Integrated	Drag answer here	Integrated

What is determined by the "MaxConcurrentConnections" setting within a platform?

Options:

A- maximum number of concurrent connections that can be opened between the CPM and the remote machines for the platform

B- maximum number of concurrent connections that can be between the PSM and the remote machines for the platform

C- maximum number of concurrent connections allowed for a specific account on the platform through the PSM

D- maximum number of concurrent connections to the Vault allowed for sending audit activities relating to the platform

Answer:
A

Question 9

Question Type: **MultipleChoice**

If a customer has one data center and requires fault tolerance, how many PVWAs should be deployed?

Options:

A- two or more

B- one PVWA cluster

C- one

D- two PVWA clusters

Answer:

A

Question 10

Question Type: **MultipleChoice**

After installing the first PSM server and before installing additional PSM servers, you must ensure the user performing the installation is not a direct owner of which safe?

Options:

A- PSMUnmanagedSessionAccounts Safe

B- PSMRecordingsSessionAccounts Safe

C- PSMUnmanagedApplicationAccounts Safe

D- PSMSessionBackupAccounts Safe

Answer:

A

Question 11

Question Type: MultipleChoice

You are installing a CPM.

In addition to Add Safes, Add/Update Users, Reset Users' Passwords and Manage Server File Categories, which Vault authorization(s) does a CyberArk user need to install the CPM?

Options:

A- Manage Directory Mapping

B- Activate Users

C- Backup All Safes, Restore All Safes

D- Audit Users, Add Network Areas

Answer:

B

Question 12

Question Type: **MultipleChoice**

You are configuring SNMP remote monitoring for your organization's Vault servers.

In the PARAgent.ini, which parameter specifies the destination of the Vault SNMP traps?

Options:

A- SNMPHostIP Most Voted

B- SNMPTrapPort

C- SNMPCommunity

D- SNMPVersion

Answer:

A