



Free Questions for DES-1111 by dumpssheet

Shared by Jackson on 24-05-2024

For More Free Questions and Preparation Resources

Check the Links on Last Page

Question 1

Question Type: MultipleChoice

A storage architect is planning a Unisphere upgrade. Which password is required for the upgrade?

Options:

- A- lockbox
- B- root
- C- sysadmin
- D- boxmgmt

Answer:

A

Question 2

Question Type: MultipleChoice

A storage administrator is unable to terminate the TimeFinder SnapVX snapshot. What action should be performed by the administrator?

Options:

- A- Modify the Time to Live setting
- B- Verify that there are no linked targets or restore sessions
- C- Run a terminate command for each individual LUN
- D- Check if there is an available reserved capacity

Answer:

B

Question 3

Question Type: MultipleChoice

Data is being migrated from a VNX to a PowerMax using Open Replicator. The Pace Value is 0 with a Ceiling of 10%. Copies are taking a very long time to complete.

What could be done to resolve this issue?

Options:

- A- Set Pace to 10; set Ceiling to 0%
- B- Set Pace to 10; set Ceiling to 100%
- C- Leave Pace as-is; set Ceiling to None
- D- Leave Pace as-is; set Ceiling to 100%

Answer:

D

Question 4

Question Type: MultipleChoice

Which view of the Unisphere for PowerMax user interface can an architect go to for a heatmap?

Options:

- A- Selected System > System
- B- All Systems > Performance
- C- All Systems > Databases
- D- Selected System > Dashboard

Answer:

B

Question 5

Question Type: MultipleChoice

Which SRDF/A resiliency feature allows sessions to remain active during transient link outages?

Options:

- A- Group-Level Write Pacing
- B- Transmit Idle
- C- Recovery After Link Loss

D- Failback

Answer:

B

Question 6

Question Type: MultipleChoice

A customer is planning to implement SRDF/Metro, using the default Device Bias method. What is a consideration?

Options:

- A-** Bias cannot be changes in the SRDF/Metro group.
- B-** This setting applies to all SRDF groups in both arrays.
- C-** There is no way to make the R2 device available to the host.
- D-** The state of the device pair is ActiveActive.

Answer:

C

To Get Premium Files for DES-1111 Visit

<https://www.p2pexams.com/products/des-1111>

For More Free Questions Visit

<https://www.p2pexams.com/dell-emc/pdf/des-1111>

