



Free Questions for 4A0-N02 by dumpssheet

Shared by Tyson on 24-05-2024

For More Free Questions and Preparation Resources

Check the Links on Last Page

Question 1

Question Type: MultipleChoice

Which of the following statements about uplink ingress policing is FALSE?

Options:

- A- It can be applied to the overlay.
- B- It can be applied to the underlay.
- C- VSD raises an alarm when the policing threshold is crossed.
- D- The policer can be configured by enterprise admin.

Answer:

B

Question 2

Question Type: MultipleChoice

Which of the following is correct about the NAT/PAT function on the NSG?

Options:

- A-** Only one mode (either NAT or PAT) is supported, depending on administrative configuration.
- B-** NAT/PAT is used to offload the Internet traffic.
- C-** By default, NAT/PAT is enabled.
- D-** NAT/PAT is enabled at the NSG level and applied to all network ports.

Answer:

B

Question 3

Question Type: MultipleChoice

Which of the following VSD service abstractions maps to a VRF instance in standard networking terminology?

Options:

- A- Domain
- B- Zone
- C- Subnet
- D- L2 domain

Answer:

A

Question 4

Question Type: MultipleChoice

Which of the following statements about an egress QoS policy is FALSE?

Options:

- A- It assigns the child queue rate limiters to the queues.

- B-** All 8 forwarding classes must be assigned to one or more queues.
- C-** The sum of the GIR of the queues must be less than or equal to the GIR of the parent.
- D-** The sum of the PIR of the queues must be less than or equal to the PIR of the parent.

Answer:

C

Question 5

Question Type: MultipleChoice

Which of the following interfaces is not supported on VSC?

Options:

- A-** API interface
- B-** BGP interface
- C-** OpenFlow interface
- D-** XMPP interface

Answer:

A

Question 6

Question Type: MultipleChoice

Which statement is FALSE regarding the vport?

Options:

- A-** NSG vPorts are associated with access ports.
- B-** There are four types of vPorts: VM, container, host and bridge.
- C-** The NSG's vPorts are typically host vPorts.
- D-** One vPort can only belong to one subnet or L2 domain.

Answer:

B

Question 7

Question Type: MultipleChoice

Which of the following is true about Nuage Networks NSG-E?

Options:

- A- It is a virtual appliance.
- B- It has 4 LAN ports at maximum.
- C- It supports dual WAN uplinks.
- D- It can only be deployed in standalone model.

Answer:

C

Question 8

Question Type: MultipleChoice

During VNS automated site activation, the domain design and attributes are configured on which of the following device?

Options:

- A- VSD (Virtualized Services Directory)
- B- VSC (Virtualized Services Controller)
- C- NSG (Network Services Gateway)
- D- Installer PC

Answer:

C

To Get Premium Files for 4A0-N02 Visit

<https://www.p2pexams.com/products/4a0-n02>

For More Free Questions Visit

<https://www.p2pexams.com/nokia/pdf/4a0-n02>

