



**Free Questions for 4A0-104 by go4braindumps**

**Shared by Fox on 20-10-2022**

**For More Free Questions and Preparation Resources**

**Check the Links on Last Page**

## Question 1

---

**Question Type:** MultipleChoice

---

An SDP using GRE encapsulation is configured for an E-pipe service. The network port used by the SDP has an MTU of 8000. What value does the SDP path MTU have by default on an Alcatel-Lucent 7750 SR?

**Options:**

---

A- 7958

B- 7978

C- 8022

D- 8042

**Answer:**

---

A

## Question 2

---

**Question Type:** MultipleChoice

---

On which object is ADSPEC enabled?

**Options:**

---

- A- SDP
- B- Network port
- C- LSP
- D- Service
- E- RSVP

**Answer:**

---

C

## Question 3

---

**Question Type:** MultipleChoice

---

A VPLS has a service MTU of 1600. To create an IES spoke termination to the VPLS, what ip-mtu value must be used for the IES?

**Options:**

---

A- 1586

B- 1596

C- 1600

D- 1614

**Answer:**

---

A

## Question 4

---

**Question Type: MultipleChoice**

---

What Alcatel-Lucent 7750 SR OAM tool can be used to verify the end-to-end connectivity of a service?

**Options:**

---

A- Sdp-ping

- B- Isp-ping
- C- Svc-ping
- D- Sdp-mtu

**Answer:**

---

C

## Question 5

---

**Question Type:** MultipleChoice

---

Which of the following is a characteristic of a VPLS?

**Options:**

---

- A- All SAPs of a VPLS belong to the same broadcast domain.
- B- When a new site is added, all the existing sites need to be shutdown and re-provisioned.
- C- An additional T-LDP session is required between PEs for each additional VPLS that is provisioned.
- D- Multiple VPLSes on the same router share a single MAC FDB

**Answer:**

---

A

## Question 6

---

**Question Type: MultipleChoice**

---

Which of the following about ADSPEC is FALSE?

**Options:**

---

- A-** ADSPEC sets an SDP's MTU to the smallest MTU value found along the LSP path.
- B-** RSVP must be enabled on all MPLS routers of a path to use ADSPEC
- C-** ADSPEC can automatically adjust the service MTU
- D-** ADSPEC can be enabled on individual LSPs.

**Answer:**

---

C

## Question 7

---

**Question Type:** MultipleChoice

---

What happens by default on an Alcatel-Lucent 7750 SR when a null encapsulated SAP receives a frame with a VLAN tag?

### Options:

---

- A- The original VLAN tag is removed.
- B- The original VLAN tag is kept.
- C- The VLAN tag is replaced by a provider tag.
- D- The VLAN tag is kept and a provider tag is added.

### Answer:

---

B

## Question 8

---

**Question Type:** MultipleChoice

---

On an Alcatel-Lucent 7750 SR, which vc-type will strip service delimiting tags at the ingress PE?

**Options:**

---

- A- vc-type ether
- B- vc-type vlan
- C- vc-type dot1q
- D- vc-type null

**Answer:**

---

A

## Question 9

---

**Question Type: MultipleChoice**

---

When configuring distributed services across a network, it is considered best practice to configure which of the following parameters as globally significant?



**Options:**

---

- A- Customer ID and SAP ID
- B- Customer ID and Service ID
- C- SAP ID and Service ID
- D- SDP ID and Service ID
- E- SDP ID and SAP ID
- F- SDP ID and VC ID

**Answer:**

---

B

## Question 10

---

**Question Type: MultipleChoice**

---

In a Layer 2 encapsulation using T-LDP, what does the first (top) label represent?

**Options:**

---

**A-** Tunnel Label

**B-** VC Label

**C-** Operational Control Word

**D-** UNI

**E-** NNI

**Answer:**

---

A

**To Get Premium Files for 4A0-104 Visit**

<https://www.p2pexams.com/products/4a0-104>

**For More Free Questions Visit**

<https://www.p2pexams.com/nokia/pdf/4a0-104>

