



Free Questions for H11-851_V3.0 by actualtestdumps

Shared by Acevedo on 24-05-2024

For More Free Questions and Preparation Resources

Check the Links on Last Page

Question 1

Question Type: MultipleChoice

SMC3.0 supports multiple ways to create meetings, including ().

Options:

- A- SMC Platform Call
- B- Adhoc
- C- OA Plugin
- D- Call set

Answer:

A, B, C, D

Question 2

Question Type: MultipleChoice

A company is now going to hold a provincial seminar that requires the City A Convention Center and the City B Conference Center to join in. A City Convention Center commonly uses the A meeting

template to hold meetings, and the center commonly uses the B meeting template to hold meetings. From the perspective of feasibility and ease of operation, ().

Options:

A- Adhoc

B- VR dial-up to

C- The main caller is called the call set

D- Multi-level conference

Answer:

D

Question 3

Question Type: MultipleChoice

() Only unmanageable additions to SMC2.0 are supported.

Options:

A- TE10

B- P3206

C- Box300

D- RP100

Answer:

A

Question 4

Question Type: MultipleChoice

SMC2.0 scheduled meetings can not be held normally, what are the possible reasons?

Options:

- A- Registration for GK at some venues for the scheduled meeting failed.
- B- Some of the venue network failures for the scheduled meeting.
- C- The MCU resources used for this scheduled meeting are insufficient.
- D- The MCU used for the scheduled meeting is offline.

Answer:

A, B, C, D

Question 5

Question Type: MultipleChoice

SMC2.0 supports inspection types of devices including ().

Options:

- A- Terminal
- B- SC
- C- MCU

D- Recording

Answer:

A, C, D

Question 6

Question Type: MultipleChoice

What is the following description of the VMR meeting incorrect?

Options:

- A-** A VRM number can only support one meeting at a time.
- B-** All VMR meetings require the meeting to be activated before the other venues can be enrolled.
- C-** VMR conferencing does not consume the MCU's resources when it is not activated.
- D-** When adding a venue on SMC2.0, you can configure the VMR number directly for the terminal.

Answer:

A

Question 7

Question Type: MultipleChoice

During SVC conferences, the terminal sends up to the MCU() code stream, including secondary streams and mainstream streams, with resolutions between 90p and 720p.

Options:

A- 2

B- 4

C- 6

D- 8

Answer:

B

Question 8

Question Type: MultipleChoice

After modifying the "networking mode", the VP98 series MCU requires a server restart to take effect.

Options:

A- True

B- False

Answer:

A

Question 9

Question Type: MultipleChoice

() is a multiviewer mode supported by cloudMCU.

Options:

- A- Divided into 24 screens
- B- A large number of small Ontable modes
- C- Divided into 9 screens
- D- Divided into 16 screens equally

Answer:

A, B, C, D

Question 10

Question Type: MultipleChoice

The Media board of the VP96 series MCUs can complete the adaptation of audio and video media, and the single Media board supports () 1080p30 media processing capacity up to a maximum of

1080p30.

Options:

A- 32

B- 64

C- 24

D- 12

Answer:

A

To Get Premium Files for H11-851_V3.0 Visit

https://www.p2pexams.com/products/h11-851_v3.0

For More Free Questions Visit

<https://www.p2pexams.com/huawei/pdf/h11-851-v3.0>

