

# Free Questions for H12-211 by vceexamstest

Shared by Allen on 24-05-2024

For More Free Questions and Preparation Resources

**Check the Links on Last Page** 

# **Question 1**

**Question Type:** MultipleChoice

In standard STP mode, which of the following non-root switches forwards the TC set BPDU generated by the root switch?

#### **Options:**

- A) Root port
- B) Backup port
- C) Designated port
- D) Provisioning port

#### **Answer:**

С

# **Question 2**

**Question Type:** MultipleChoice

Which of the following functions does the Ctrl+Z key combination have in the VRP system? (multiple choice)

#### **Options:**

- A) Return from the system view to the user view
- B) Exit the current view
- C) Exit interface view
- D) Exit the Console interface view
- E) Return from any view to the user view

#### **Answer:**

A, B, C, D, E

# **Question 3**

**Question Type:** MultipleChoice

system view

[Huawei]command privilege level 3 view user save

The correct statement about the above configuration command is ()

#### **Options:**

- A) Modify the save command of a user to have a permission level of 3
- B) Modify the permission level of the save command in the user view to 3
- C) Modify the user view command to a permission level of 3, and save the configuration
- D) Modify the user's permission level to 3, and save the configuration

#### **Answer:**

В

### **Question 4**

#### **Question Type:** MultipleChoice

When RIPv1 is enabled on the Huawei router, the interface that is advertised to the RIP receives the RIPv1 broadcast packet, the RIPv2 broadcast packet, and the multicast packet by default.

| Options:  |
|---|
| A) Yes  |
| B) Wrong  |
| Answer:   |
| A   |
| Question 5  |
| Question Type: MultipleChoice   |
| When two OSPF routers form a TWO WAY-neighbor relationship, the LSDB has completed synchronization, but the SPF algorithm has not been run. |
| Options:  |
| A) Yes  B) Wrong  |
| viong   |

| Answer:  |  |
|--|--|
| В  |  |
|  |  |
| uestion 6  |  |
| uestion Type: MultipleChoice   |  |
| The Layer 2 switch belongs to the data link layer device and can identify the data according to the MAC address, and | e MAC address information in the data frame, forward the |
| Some MAC addresses and corresponding port information are recorded in  | their own internal MAC address table.                    |
|  |  |
| Options: A) Yes  |  |
| B) Wrong   |  |
|  |  |
| Answer:  |  |

A

# **Question 7**

#### **Question Type:** MultipleChoice

As shown in the broadcast network, OSPF runs on four routers and is in the same area and on the same network segment. OSPF

A DR and multiple BDRs will be automatically elected to achieve better backup results.



#### **Options:**

A) Yes

B) Wrong

#### **Answer:**

В

# **Question 8**

| <b>Question Ty</b> | pe: Multi | pleChoice |
|--------------------|-----------|-----------|
|--------------------|-----------|-----------|

From the perspective of project cutover, there is no need to back up or adjust the configuration file when upgrading the VRP system, because the lost files can be retrieved in the recycle bin.

### **Options:**

A) Yes

B) Wrong

#### **Answer:**

В

### **To Get Premium Files for H12-211 Visit**

https://www.p2pexams.com/products/h12-211

### **For More Free Questions Visit**

https://www.p2pexams.com/huawei/pdf/h12-211

