Free Questions for H35-210 by actualtestdumps

Shared by Tyler on 24-05-2024

For More Free Questions and Preparation Resources

Check the Links on Last Page

Question 1

Question Type: MultipleChoice

(single) Is the following description correct? The FTTx device offline deployment solution is to generate offline device configuration data through network planning data. After the device is powered on, the configuration data is automatically delivered to achieve the plug-and-play function of the device.

Options:

A- True

B- False

Answer:

A

Question 2

Question Type: MultipleChoice

(single) Is the following description correct? When creating an ADSL line configuration template, the MA5600T can specify the template number or not. If not specified, the system automatically assigns the smallest idle template number.

Options:

A- True

B- False

Answer:

A

Question 3

Question Type: **MultipleChoice**

(single) Is the following description correct? The MA5680T supports traffic shaping for specific service-ports.

Options:

A- True

B- False

Answer:

B

Question 4

Question Type: **MultipleChoice**

(multiple) The MA5680T uses the template to configure the GPON ONT template. What are the templates to be configured?

Options:

A- DBA template

B- GPON ONT line template

C- GPON ONT service template

D- GPON ONT capability template

Answer:

A, B, C

Question 5

Question Type: MultipleChoice

(single) Is the following description correct? The OLT supports the direct copying of user packet priorities as the priority of forwarding packets. It also supports local setting of priorities directly on the OLT.

Options:

A- True

B- False

Answer:

A

Question 6

Question Type: MultipleChoice

(multiple) Types of northbound interfaces provided by the U2000 to the network management layer include?

Options:

A- XML northbound interface

B- CORBA northbound interface

C- SNMP alarm northbound interface

D- TL1 northbound interface

Answer:

A, B, C, D

Question 7

Question Type: MultipleChoice

The vlan of the user side is usually converted to vlan on the MA5680T service board. What are the vlan conversion methods?

Options:

A- transparent

B- translate

C- add-double

D- translate-and-transparent

Answer:

A, B, C

Question 8

Question Type: **MultipleChoice**

(multiple) What are the operations that need to be performed when adding an ONT to the MA5680T?

Options:

A- Configure the DBA template

B- Configure the ONT line template

C- Configure the ONT service template.

D- Add ONT and bind related templates

Answer:

A, B, C, D

Question 9

Question Type: MultipleChoice

(single) Which of the following is incorrect about GPON?

Options:

A- Each GPON port, with a 1:64 split ratio, provides 64 ONT access.

B- There can be multiple T-CONTs on each ONU, and each TCONT can be tied to multiple GEMPORTs.

C- T-CONT is equivalent to a physical cache, and only the DBA template is bound to limit the speed.

D- ONU ID must be unique on the OLT

Answer:

D

Question 10

Question Type: MultipleChoice

(multiple) The UA5000 uses the supervlan command to add multiple sub VLANs to a super VLAN. Which VLAN types can be used for the Sub VLAN?

Options:

A- super vlan

B- standard vlan

C- mux vlan

D- smart vlan

Answer:

B, C, D

Question 11

Question Type: MultipleChoice

(multiple) What do I need to configure when adding the ont-lineprofile to the MA5680T?

Options:

A- Configure the vlan of the ONT ETH port.

B- Add DBA template

C- Binding tcont and DBA templates

D- Increase gemport and configure gemport mapping

Answer:

C, D

To Get Premium Files for H35-210 Visit

https://www.p2pexams.com/products/h35-210

For More Free Questions Visit

https://www.p2pexams.com/huawei/pdf/h35-210