



Free Questions for JN0-635 by dumpshq

Shared by Valentine on 06-06-2022

For More Free Questions and Preparation Resources

Check the Links on Last Page

Question 1

Question Type: MultipleChoice

You are asked to look at a configuration that is designed to take all traffic with a specific source ip address and forward the traffic to a traffic analysis server for further evaluation. The configuration is no longer working as intended.

Referring to the exhibit which change must be made to correct the configuration?

Options:

- A- Apply the filter as in input filter on interface xe-0/2/1.0
- B- Apply the filter as in input filter on interface xe-0/0/1.0
- C- Create a routing instance named default
- D- Apply the filter as in output filter on interface xe-0/1/0.0

Answer:

B

Question 2

Question Type: MultipleChoice

Exhibit.

```
[edit]
user@erx# show system security-profile
SP-1 {
    policy {
        maximum 100;
        reserved 50;
    }
    zone {
        maximum 100;
        reserved 50;
    }
    nat-nopat-address {
        maximum 115;
        reserved 100;
    }
    nat-static-rule {
        maximum 125;
        reserved 100;
    }
}
```

```
[edit]
user@erx# show tenants
C-1 {
    security-profile {
        SP-1;
    }
}
```

Referring to the exhibit, which two statements are true? (Choose two.)

Options:

- A-** The c-1 TSYS has a reservation for the security flow resource.
- B-** The c-1 TSYS can use security flow resources up to the system maximum.
- C-** The c-1 TSYS cannot use any security flow resources.
- D-** The c-1 TSYS has no reservation for the security flow resource.

Answer:

C, D

Explanation:

https://www.juniper.net/documentation/en_US/junos/topics/topic-map/security-profile-logical-system.html

Question 3

Question Type: MultipleChoice

What are two important function of the Juniper Networks ATP appliance solution? (Choose two.).

Options:

- A- Statistics
- B- Analysis
- C- Detection
- D- Filtration

Answer:

B, C

Explanation:

<https://www.juniper.net/us/en/products-services/security/advanced-threat-prevention/>

Question 4

Question Type: MultipleChoice

Which three type of peer devices are supported for Cos-Based IPsec VPN?

Options:

- A- High-end SRX Series device
- B- cSRX
- C- vSRX
- D- Branch-end SRX Series devices

Answer:

A, C, D

Question 5

Question Type: MultipleChoice

You have the NAT rule, shown in the exhibit, applied to allow communication across an IPsec tunnel between your two sites with identical networks. Which statement is correct in this scenario?

Options:

- A- The NAT rule will translate the source and destination addresses.
- B- The NAT rule will only translate two addresses at a time.
- C- The NAT rule is applied to the N/A routing instance.
- D- 10 packets have been processed by the NAT rule.

Answer:

A

Question 6

Question Type: MultipleChoice

You are connecting two remote sites to your corporate headquarters site; you must ensure that all traffic is secured and only uses a single Phase 2 SA for both sites.

In this scenario, which VPN should be used?

Options:

- A- An IPsec group VPN with the corporate firewall acting as the hub device.
- B- Full mesh IPsec VPNs with tunnels between all sites.
- C- A hub-and-spoke IPsec VPN with the corporate firewall acting as the hub device.
- D- A full mesh Layer 3 VPN with the corporate firewall acting as the hub device.

Answer:

A

Explanation:

<https://www.juniper.net/us/en/local/pdf/app-notes/3500202-en.pdf>

Question 7

Question Type: MultipleChoice

Exhibit.

```
[edit security ike gateway advpn-gateway]
user@srx# show
ike-policy advpn-policy;
address 192.168.3.1;
local-identity distinguished-name;
remote-identity distinguished-name container O=Juniper;
external-interface ge-0/0/3.0;
advpn {
  partner {
    disable;
  }
}
version v2-only;

[edit interfaces]
user@srx# show st0
unit 0 {
  multipoint;
  family inet {
    address 10.100.100.1/24;
  }
}
```

Referring to the exhibit, a spoke member of an ADVPN is not functioning correctly.

Which two commands will solve this problem? (Choose two.)

Options:

A- [edit interfaces]

```
user@srx# delete st0.0 multipoint
```

B- [edit security ike gateway advpn-gateway]

```
user@srx# delete advpn partner
```

C- [edit security ike gateway advpn-gateway]

```
user@srx# set version v1-only
```

D- [edit security ike gateway advpn-gateway]

```
user@srx# set advpn suggerter disable
```

Answer:

B, D

Explanation:

https://www.juniper.net/documentation/en_US/junos/topics/topic-map/security-auto-discovery-vpns.html

Question 8

Question Type: MultipleChoice

You are asked to configure a security policy on the SRX Series device. After committing the policy, you receive the "Policy is out of sync between RE and PFE ." error.

Which command would be used to solve the problem?

Options:

- A- request security polices resync
- B- request service-deployment
- C- request security polices check
- D- restart security-intelligence

Answer:

A

Explanation:

https://kb.juniper.net/InfoCenter/index?page=content&id=KB30443&cat=SRX_SERIES&actp=LIST

Question 9

Question Type: MultipleChoice

You must implement an IPsec VPN on an SRX Series device using PKI certificates for authentication. As part of the implementation, you are required to ensure that the certificate submission, renewal, and retrieval processes are handled

automatically from the certificate authority.

In this scenario, which statement is correct.

Options:

- A- You can use CRL to accomplish this behavior.
- B- You can use SCEP to accomplish this behavior.
- C- You can use OCSP to accomplish this behavior.
- D- You can use SPKI to accomplish this behavior.

Answer:

B

Explanation:

Certificate Renewal The renewal of certificates is much the same as initial certificate enrollment except you are just replacing an old certificate (about to expire) on the VPN device with a new certificate. As with the initial certificate request, only manual renewal is supported. SCEP can be used to re-enroll local certificates automatically before they expire. Refer to Appendix D for more details.

Question 10

Question Type: MultipleChoice

You are not able to activate the SSH honeypot on the all-in-one Juniper ATP appliance.

What would be a cause of this problem?

Options:

- A- The collector must have a minimum of two interfaces.
- B- The collector must have a minimum of three interfaces.
- C- The collector must have a minimum of five interfaces.
- D- The collector must have a minimum of four interfaces.

Answer:

D

Explanation:

https://www.juniper.net/documentation/en_US/release-independent/jatp/topics/task/configuration/jatp-traffic-collectorsetting-ssh-honeypot-detection.html

Question 11

Question Type: MultipleChoice

You have a webserver and a DNS server residing in the same internal DMZ subnet. The public Static NAT addresses for the servers are in the same subnet as the SRX Series devices internet-facing interface. You implement DNS doctoring to ensure remote users can access the webserver. Which two statements are true in this scenario? (Choose two.)

Options:

- A- The DNS doctoring ALG is not enabled by default.
- B- The Proxy ARP feature must be configured.
- C- The DNS doctoring ALG is enabled by default.
- D- The DNS CNAME record is translated.

Answer:

B, C

To Get Premium Files for JN0-635 Visit

<https://www.p2pexams.com/products/jn0-635>

For More Free Questions Visit

<https://www.p2pexams.com/juniper/pdf/jn0-635>

