Question 1

The recommended way to implement a service wrapper hook that customizes the authenticateByScreenName() method of the User service using a class called com.sample.MyUserLocalServiceImpl is to: (Please select all correct answers.)

Options:

A- Add the following to liferay-hook.xml:

<service>

<service-type>com.liferay.portal.service.UserLocalService</service-type>

<service-impl>com.sample.MyUserLocalServiceImpl</service-impl>

</service>

B- Copy all of the methods from UserLocalServiceImpl to MyUserLocalServiceImpl

C- Override the authenticateByScreenName() method in MyUserLocalServiceImpl

D- Add the following to liferay-plugin-package.properties: required -deployment-contexts=UserLocalServ ice

E- Implement custom logic and call super.authenticateByScreenNameQ if applicable

Answer:

A, C, E

Question 2

The recommended way to customize how the User object indexes information is through a(n):

Options:

A- Hook plugin

B- Direct modification of the portal source

C- Ext plugin

D- Ext environment

Answer:

A

Question 3

The method to get theme settings in a theme is:

Options:

A- $portalUtil.getSetting()

B- $theme.getSetting()

C- $layout.getSetting()

D- $themeDisplay.getSetting()

Answer:

B

Question 4

Question Type: **MultipleChoice**

The following code:

GetterUtil.getInteger("one")

returns:

Options:

A- 0

B- 1

C- The code throws a java.lang.ArithmeticException

D- The code throws a com.liferay.portal.kernel.exception.SystemException

Answer:

A

Question 5

Question Type: **MultipleChoice**

When embeddding a plugin portlet in a layout template with $processor.processPortlet() use the:

A- Portlet name

B- Fully qualified portlet ID

C- Portlet URL

D- Fully qualified display name

Answer:

B

Question 6

Question Type: MultipleChoice

After a portlet completes the action phase:

Options:

A- Only that portlet enters the render phase

B- All portlets on the page enter the render phase

C- Any portlet whose data has changed enters the render phase

D- Nothing happens since the render phase occurs before the action phase

Answer:

B

Question 7

Question Type: MultipleChoice

Tables are created in the database for a Service Builder entity after:

Options:

A- The Ant 'build-service' target has run

B- The portlet is deployed for the first time

C- The portlet is added to a page for the first time

D- Tables must be created manually

Answer:

B

Question 8

Question Type: MultipleChoice

The recommended way to add a custom class to Liferay's startup process is to:

Options:

A- Create a portal-ext.properties file in the Liferay Home directory that adds the custom class to global.startup.events, and add the custom class to the deployed Liferay application

B- Create an Ext plugin that replaces the value of global.startup.events with the custom class, and add the custom class to the plugin

C- Create a portal-ext.properties file in the Liferay Home directory that replaces the value of global.startup.events with the custom class, and add the custom class to portal-impl.jar

D- Create an Ext plugin that adds the custom class to global.startup.events, and add the custom class to the plugin

Answer:

D

Question 9

Advantages of hook plugins over Ext plugins include: (Please select all correct answers.)

Options:

A- A hook plugin is hot deployable, while an Ext plugin is not

B- A hook plugin has direct access to the portal class loader, while an Ext plugin does not

C- A hook plugin provides an easier upgrade path for overriding core services and JSPs

D- A hook plugin can modify service layer classes, while an Ext plugin cannot

Answer:

A, C

Question 10

The JavaScript method that executes as soon as the HTML document has finished loading is:

Options:

A- AUI().ready(fn)

B- Liferay.Portlet.ready(fn)

C- Liferay.on(fn)

D- None of the above

Answer:

A

Question 11

AlloyUI is:

Options:

A- A JavaScript library

B- A CSS framework

C- A tag library

D- All of the above

Answer:

D