Question 1

What happens when the command getfattr afile is run while the file afile has no extended attributes set?

Options:

A- getfattr prints a warning and exits with a values of 0.

B- getfattr prints a warning and exits with a value of 1.

C- No output is produced and getfattr exits with a value of 0.

D- No outputs is produced and getfattr exits with a value of 1

Answer:

C

Question 2

What option of mount.cifs specifies the user that appears as the local owner of the files of a mounted CIFS share when the server does not provide ownership information? (Specify ONLY the option name without any values or parameters.)

Answer:

Explanation:

http://linux.die.net/man/8/mount.cifs

Question 3

Question Type: **FillInTheBlank**

Which command is used to run a new shell for a user changing the SELinux context? (Specify ONLY the command without any path or parameters.)

Answer:

Explanation:

Question 4

Question Type: **MultipleChoice**

Which of the following access control models is established by using SELinux?

Options:

A- Security Access Control (SAC)

B- Group Access Control (GAC)

C- User Access Control (UAC)

D- Discretionary Access Control (DAC)

E- Mandatory Access Control (MAC)

Question 5

Question Type: MultipleChoice

Which of the following authentication methods was added to NFS in version 4?

Options:

A- Kerberos authentication

B- SSH hostkey authentication

C- Winbind authentication

D- SSL certificate authentication

Answer:

A

Question 6

Which command revokes ACL-based write access for groups and named users on the file afile?

Options:

A- setfacl -x group: * : rx, user:*: rx afile

B- setfacl -x mask: : rx afile

C- setfacl ~m mask: : rx afile

D- setfacl ~m group: * : rx, user:*: rx afile

Answer:

C

Question 7

Which option of the openvpn command should be used to ensure that ephemeral keys are not written to the swap space?

Options:

A- --mlock

B- --no-swap

C- --root-swap

D- --keys-no-swap

Answer:

A

Question 8

Question Type: **FillInTheBlank**

Which option in an Apache HTTPD configuration file enables OCSP stapling? (Specify ONLY the option name without any values or parameters.)

Question 9

Question Type: MultipleChoice

What is the purpose of the program snort-stat?

Options:

A- It displays statistics from the running Snort process.

B- It returns the status of all configured network devices.

C- It reports whether the Snort process is still running and processing packets.

D- It displays the status of all Snort processes.

E- It reads syslog files containing Snort information and generates port scan statistics.

Answer:

E

Question 10

Which of the following statements are true regarding the certificate of a Root CA? (Choose TWO correct answers.)

Options:

A- It is a self-signed certificate.

B- It does not include the private key of the CA

C- It must contain a host name as the common name.

D- It has an infinite lifetime and never expires.

E- It must contain an X509v3 Authority extension.

Answer:

A, B, E

Question 11

Which of the following commands makes the contents of the eCryptfs encrypted directory -/Private available to the user?

Options:

A- ecryptfsclient

B- ecryptfs.mount

C- ecryptfs-mount-private

D- decryptfs

E- ecryptfs-manage-di rectory

Answer:

C