



**Free Questions for 4A0-104 by dumpssheet**

**Shared by Warner on 24-05-2024**

**For More Free Questions and Preparation Resources**

**Check the Links on Last Page**

## Question 1

---

**Question Type:** MultipleChoice

---

Customer 'A' has sites on 3 different Alcatel-Lucent PE routers. The routers are connected to each other through an IP/MPLS network in a full mesh fashion. Customer 'A' requires a VPLS service. Which of the following statements are TRUE? (Choose2)

### Options:

---

- A) Each router requires 1 VPLS service.
- B) Each router requires 2 VPLS services.
- C) Each router requires 1 SDP with 2 LSPs, one to each of the other 2 routers.
- D) Each router requires 2 SDPs.
- E) Each router requires 3 SDPs

### Answer:

---

A, D

## Question 2

---

**Question Type: MultipleChoice**

---

What is the purpose of service mirroring on the Alcatel-Lucent Service Router?

**Options:**

---

- A) To mirror service requirements of a customer with a single branch office and multiple remote sites
- B) To utilize unused ports of a service router until they are required for a service.
- C) To replicate traffic from a service port to another port for debugging or monitoring functions
- D) To ease the configuration burden of services that support a large number of subscribers
- E) All of the above

**Answer:**

---

C

## Question 3

---

**Question Type: MultipleChoice**

---

Which of the following about the components of a service on the Alcatel-Lucent 7750 SR is FALSE?

**Options:**

---

- A) An SDP can be used by more than one service and customer.
- B) A SAP can only be created on an access port.
- C) A customer can have multiple services associated to it.
- D) A customer is only created on one site of a distributed service.

**Answer:**

---

D

## Question 4

---

**Question Type: MultipleChoice**

---

By default, what does an Alcatel-Lucent 7750 SR do to support VPLS services for different customers?

**Options:**

---

- A) Dedicates a separate port for each customer.
- B) Performs ARP look-ups for each service.
- C) Maintains a different IP routing table for each service.
- D) Maintains a different MAC Forwarding Database for each service.

**Answer:**

---

D

## Question 5

---

**Question Type:** MultipleChoice

---

Which one of the following items CANNOT be used as a mirror source on an Alcatel-Lucent 7750 SR?

**Options:**

---

- A) IP filter
- B) MAC filter
- C) Egress label

D) Ingress label

**Answer:**

---

C

## Question 6

---

**Question Type: MultipleChoice**

---

Which of the following about the Alcatel-Lucent 7750 SR's sdp-ping utility is FALSE?

**Options:**

---

- A) It tests uni-directional or round-trip in-band connectivity.
- B) It tests the reachability of hosts that are using an SDP.
- C) It tests the reachability of the far-end IP address of an SDP through its tunnel.
- D) It can be used by specifying only an SDP ID.

**Answer:**

---

B


## Question 7

---

**Question Type:** MultipleChoice

---

Click the exhibit.



PE1 and PE2 are Alcatel-Lucent 7750 SRs. What needs to be added to PE1's configuration to mirror traffic between PE2 and the customer site?

### Options:

---

- A) A 'remote-source' needs to be added to the mirror destination on PEL
- B) A mirror source needs to be added to PE1 with a 'remote-source'.
- C) This is not possible since the protocol analyzer is located at the Central Office. It needs to be at the customer site.
- D) A mirror source with SAP 1/1/2 needs to be added on PEL

**Answer:**

---

A

## Question 8

---

**Question Type:** MultipleChoice

---

On an Alcatel-Lucent 7750 SR, the OAM command 'svc-ping' can be used with options 'local-sdp' and 'remote-sdp'. Which of the following is TRUE?

**Options:**

---

- A) 'local-sdp' and 'remote-sdp' indicate that all services using these SDPs are pinged.
- B) 'local-sdp' and 'remote-sdp' indicate that pings are initiated from both local and remote routers.
- C) Both 'local-sdp' and 'remote-sdp' take parameters to specify which SDPs are used for the test.
- D) 'local-sdp' indicates that the ping is sent in-band, and 'remote-sdp' indicates the return ping is in-band.

**Answer:**

---

D



## Question 9

---

**Question Type:** MultipleChoice

---

On an Alcatel-Lucent 7750 SR, which of the following about IES interfaces is FALSE?

### Options:

---

- A) An IES can only have one interface.
- B) An IES interface can have an SDP or a SAP
- C) An IES can perform fragmentation.
- D) An IES must have an IP address assigned to it.

### Answer:

---

A

## Question 10

---

**Question Type:** MultipleChoice

---

On an Alcatel-Lucent 7750 SR, why must the MTU be explicitly set when configuring an IES spoke termination to a VPLS?

**Options:**

---

- A) By default, a VPLS signals an MTU based on the network port.
- B) By default, an IES sets its ip-mtu to the VC MTU of the VPLS
- C) By default, an IES uses an MTU value based on its SAP
- D) By default, an IES uses an MTU based on the network port.

**Answer:**

---

D

**To Get Premium Files for 4A0-104 Visit**

**<https://www.p2pexams.com/products/4a0-104>**

**For More Free Questions Visit**

**<https://www.p2pexams.com/nokia/pdf/4a0-104>**

