



**Free Questions for 4A0-107 by certsdeals**

**Shared by Finley on 24-05-2024**

**For More Free Questions and Preparation Resources**

**Check the Links on Last Page**

## Question 1

---

**Question Type:** MultipleChoice

---

Which of the following are major components of QoS functionality on the Alcatel-Lucent 7750 SR? (Choose three)

### Options:

---

- A) Microflow reservations using RSVP
- B) DSCP to EXP translation
- C) Traffic classification
- D) Automatic profiling and policy configuration
- E) Buffer memory management
- F) Traffic scheduling

### Answer:

---

C, E, F

## Question 2

---

**Question Type: MultipleChoice**

---

Which of the following are possible criteria for classifying packets at the network port ingress on the Alcatel-Lucent 7750 SR? (Choose three)

**Options:**

---

- A) The EXP bits in the MPLS header.
- B) The packet's source and destination IP addresses.
- C) The packet's DSCP bits.
- D) The dot1p bits in the frame header.
- E) The ID of an SDP that is transporting the packet.

**Answer:**

---

A, C, D

## Question 3

---

**Question Type: MultipleChoice**

---

Which of the following statements regarding policing and shaping on the Alcatel-Lucent 7750 SR are TRUE? (Choose two)

**Options:**

---

- A) The larger the configured MBS value, the lower the amount of shaping performed.
- B) When policing is enabled on the SAP-ingress, all traffic is considered as in-profile.
- C) Setting the CIR to 1000 and the PIR to max will enable shapeless policing at 1 Mbps within the SAP-egress policy.
- D) Configuring MBS to equal CBS will disable shaping.
- E) Setting the CIR and PIR to equal values disables soft-policing.

**Answer:**

---

B, E

## Question 4

---

**Question Type:** MultipleChoice

---

At which points can traffic be marked or remarked on the Alcatel-Lucent 7750? (Choose two)

**Options:**

---

- A) SAP-ingress only
- B) SAP-egress only
- C) SAP-ingress and SAP-egress
- D) Network ingress
- E) Network egress

**Answer:**

---

C, E

## Question 5

---

**Question Type: MultipleChoice**

---

A service provider is using GRE for his transport tunnel on the Alcatel-Lucent 7750 SR. How can traffic be marked as it traverses the service provider's network? (Choose two)

**Options:**

---

- A) Using dot1p bits of the 802.1q Ethernet frame header
- B) Using DSCP bits within the ToS field of the IP packet header.
- C) Using the IP precedence bits within the ToS field of the IP packet header.
- D) Using the CLP bit of the ATM cell header.
- E) Using the EXP bits of the MPLS transport label header.

**Answer:**

---

A, B

## Question 6

---

**Question Type:** MultipleChoice

---

On the Alcatel-Lucent 7750 SR, which of the following QoS-related policies can be configured on a SAP? (Choose three)

**Options:**

---

- A) The slope-policy
- B) The SAP-ingress policy

- C) The SAP-egress policy
- D) The network-queue policy
- E) The scheduler-policy

**Answer:**

---

B, C, E

**To Get Premium Files for 4A0-107 Visit**

**<https://www.p2pexams.com/products/4a0-107>**

**For More Free Questions Visit**

**<https://www.p2pexams.com/nokia/pdf/4a0-107>**

