

Free Questions for PCSAE by certsdeals

Shared by Bradford on 24-05-2024

For More Free Questions and Preparation Resources

Check the Links on Last Page

Question 1

Question Type: MultipleChoice

After executing the DeleteContext automation with all=yes argument, how would the context data of an incident present?

Options:

- A- All the data, including the incident key will be deleted, and the context data will be completely empty.
- B- No difference, the automation cannot be executed manually.
- C- All context data, including custom incident fields will be deleted, system incident fields will remain.
- D- All context data, except the incident key will be deleted.

Answer:

D

Question 2

Question Type: MultipleChoice

hat is used to trigger playbooks automatically based on the classification of an incident?
ptions:
Indicator type
Incoming mapper
Incident types
Integration configuration
nswer:

Question 3

Question Type: MultipleChoice

Which task type would be used to verify/check that an integration was enabled?

A- Standard task B- Conditional task C- Section Header task D- Data Collection task Answer: D Question 4 uestion Type: MultipleChoice An analyst wants to run a script to remove usernames from an incident before the incident becomes active in XSOAR. How can this be achieved?	Options:
C- Section Header task D- Data Collection task Answer: D Question 4 Destion Type: MultipleChoice An analyst wants to run a script to remove usernames from an incident before the incident becomes active in XSOAR. How can this be	Standard task
Answer: O Lestion 4 Lestion Type: MultipleChoice An analyst wants to run a script to remove usernames from an incident before the incident becomes active in XSOAR. How can this be	- Conditional task
Answer: Uestion 4 estion Type: MultipleChoice An analyst wants to run a script to remove usernames from an incident before the incident becomes active in XSOAR. How can this be	Section Header task
uestion 4 estion Type: MultipleChoice An analyst wants to run a script to remove usernames from an incident before the incident becomes active in XSOAR. How can this be	J- Data Collection task
Ruestion 4 Lestion Type: MultipleChoice An analyst wants to run a script to remove usernames from an incident before the incident becomes active in XSOAR. How can this be	
Luestion 4 Lestion Type: MultipleChoice An analyst wants to run a script to remove usernames from an incident before the incident becomes active in XSOAR. How can this be	Answer:
estion Type: MultipleChoice An analyst wants to run a script to remove usernames from an incident before the incident becomes active in XSOAR. How can this be)
nestion Type: MultipleChoice An analyst wants to run a script to remove usernames from an incident before the incident becomes active in XSOAR. How can this be	
An analyst wants to run a script to remove usernames from an incident before the incident becomes active in XSOAR. How can this be	uestion 4
	estion Type: MultipleChoice
Options:	Options:
A- Run an automation script in the Playground to remove usernames from the incident.	

B- Create a pre-processing rule that runs an automation script to remove usernames from the incident as it comes into XSOAR.
C- Run an automation script on the XSOAR server to remove usernames from the incident.
D- Create a playbook task to remove the usernames from the incident.
Answer:
В
Question 5
Question 5 Question Type: MultipleChoice
Question Type: MultipleChoice
Question Type: MultipleChoice
Question Type: MultipleChoice

B- Jobs

C- Pre-processing rules

D- Exclusion List

Λ	n	0	\A/	e	r	
\neg		J	AA	C		

Α

Question 6

Question Type: MultipleChoice

How can Cortex XSOAR administrators prevent junior analysts from viewing a senior analyst dashboard?

Options:

- A- Share the dashboard in Read and Edit mode for senior analysts.
- B- Share the dashboard in Read & Edit mode for senior analysts and Read Only for juniors analysts.
- C- Share the dashboard in Read and Write mode for senior analysts.
- D- Share the dashboard in Read Only mode for junior analysts and senior analysts.

Answer:

В

Question 7

Question Type: MultipleChoice

Where are incident layouts customized?

Options:

- A- Settings > Object Setup > Incidents > Layouts
- **B-** Settings > Integrations > Instance configuration
- **C-** Settings > Object Setup > Indicators > Layouts
- D- Settings > Advanced > Incident Layouts

Answer:

Α

Question 8

Question Type: MultipleChoice

Given the following context data, what would	be the expected	output of the exp	ression?
--	-----------------	-------------------	----------

Options:

- A- 1E56733826E5035233A097FCEA2046AF96EC616C
- B- E6EF5142E2553C1E442A0FFAC07636EAC61E6EDD
- C- 8D193FA162A305E4859BA8C45F5121F7265E3ABB
- D- e6ef5142e2553c1e442a0ffac07636eac61e6edd

Answer:

D

Question 9

Question Type: MultipleChoice

Which option is available in XSOAR to create the body of a Threat Intel Report?

Options:	
A- Markdown	
B- Grid Fields	
C- DOC format	
D- Javascript	
Answer:	
A	
A	
Question 10	
Question 10	
Question 10 Question Type: MultipleChoice	
Question 10	
Question 10 Question Type: MultipleChoice	
Question 10 Question Type: MultipleChoice	

- **B-** Just after the pre-processing is executed
- C- Just after the playbook is executed
- D- Just after the Close Incident button is clicked

Answer:

С

To Get Premium Files for PCSAE Visit

https://www.p2pexams.com/products/pcsae

For More Free Questions Visit

https://www.p2pexams.com/palo-alto-networks/pdf/pcsae

