Free Questions for NSE6_FSW-7.2

Shared by Thomas on 04-10-2024

For More Free Questions and Preparation Resources

Check the Links on Last Page

Question 1

Question Type: MultipleChoice

Which is a requirement to enable SNMP v2c on a managed FortiSwitch?

Options:

- A- Create an SNMP user to use for authentication and encryption.
- B- Specify an SNMP host to send traps to.
- C- Enable an SNMP v3 to handle traps messages with SNMP hosts.
- D- Configure SNMP agent and communities.

Answer:

D

Question 2

Question Type: MultipleChoice

Which Ethernet frame can create Layer 2 flooding due to all bytes on the destination MAC address being set to all FF?

Options:

- A- The broadcast Ethernet frame
- B- The unicast Ethernet frame
- **C-** The multicast Ethernet frame
- D- The anycast Ethernet frame

Answer:

Α

Question 3

Question Type: MultipleChoice

Which packet capture method allows FortiSwitch to capture traffic on trunks and management interfaces?

Options:	
A- SPAN	
B- Sniffer profile	
C- sFlow	
D- TCP dump	
Answer:	
С	
Question 4	
Question 4	•Choice
	eChoice
Question 4 uestion Type: Multiple	eChoice work administrators use to segment network operations and the administration of managed FortiSwitch devices on
Question 4 uestion Type: Multiple	
Question 4 uestion Type: Multiple What feature can net	
Question 4 uestion Type: Multiple What feature can net	

- B- Multi-chassis link aggregation trunk
- **C-** FortiGate clustering protocol
- D- FortiLink split interface

Α

Question 5

Question Type: MultipleChoice

Which two types of Layer 3 interfaces can participate in dynamic routing on FortiSwitch? (Choose two.)

Options:

- A- Detected management interfaces
- **B-** Loopback interfaces
- C- Switch virtual interfaces
- **D-** Physical interfaces

B, C

Question 6

Question Type: MultipleChoice

Refer to the exhibit.

Commands

```
config switch-controller lldp-profile
    edit "LLDP-PROFILE"
        set med-tlvs network-policy
        set auto-isl disable
        config med-network-policy
            edit "voice"
            next
            edit "voice-signaling"
            edit "quest-voice"
            next
            edit "guest-voice-signaling"
            next
            edit "softphone-voice"
            next
            edit "video-conferencing"
            next
            edit "streaming-video"
            next
            edit "video-signaling"
            next
        end
        config med-location-service
            edit "coordinates"
            next
            edit "address-civic"
            next
            edit "elin-number"
            next
        end
    next
end
                             Activate Window
```

The profile shown in the exhibit is assigned to a group of managed FortiSwitch ports, and these ports are connected to endpoints which are powered by PoE.

Which configuration action can you perform on the LLDP profile to cause these endpoints to exchange PoE information and negotiate power with the managed FortiSwitch?

0	b	ti	O	n	S	
	~	•			$\overline{}$	-

- A- Create new a LLDP-MED application type to define the PoE parameters.
- B- Assign a new LLDP profile to handle different LLDP-MED TLVs.
- C- Define an LLDP-MED location ID to use standard protocols for power.
- D- Add power management as part of LLDP-MED TLVs to advertise.

D

Question 7

Question Type: MultipleChoice

How does FortiGate handle configuration of flow tracking sampling if you export the settings to a managed FortiSwitch stack with sampling mode set to perimeter is true?

Options:

- A- FortiGate configures FortiSwitch to perform ingress sampling on all switch interfaces.
- B- FortiGate configures FortiSwitch to perform ingress sampling on all switch interfaces, except ICL and ISL interfaces.
- C- FortiGate configures and enables flow sampling on FortiSwitch but does not change existing sampling settings of interfaces.
- D- FortiGate configures and enables egress sampling on all management interfaces.

В

Question 8

Question Type: MultipleChoice

What are two ways in which automatic MAC address guarantine works on FortiSwitch? (Choose two.)

Options:

- A- FortiSwitch supports only by VLAN quarantine mode.
- B- FortiGate applies the quarantine-related configuration only on FortiGate.
- C- FortiAnalyzer with a threat detection services license is required.

D- MAC address quarantine can be enabled through the FortiGate CLI only.

Answer:

C, D

To Get Premium Files for NSE6_FSW-7.2 Visit

https://www.p2pexams.com/products/nse6_fsw-7.2

For More Free Questions Visit

https://www.p2pexams.com/fortinet/pdf/nse6-fsw-7.2

